



NTN Bearing de Mexico, S.A.



61903 Bearing 2D drawings and 3D CAD models

SKF 61903 Bearing

Bearing No. 61903

Size	30x17x7 mm
Bore Diameter	30 mm
Outer Diameter	17 mm
Width	7 mm
d	17 mm
D	30 mm
B	7 mm
d ₁	20.4 mm
D ₂	27.7 mm
r _{1,2} - min.	0.3 mm
d _a - min.	19 mm
D _a - max.	28 mm
r _a - max.	0.3 mm
Basic dynamic load rating - C	4.6 kN
Basic static load rating - C ₀	2.6 kN
Fatigue load limit - P _u	0.108 kN
Reference speed	50000 r/min
Limiting speed	32000 r/min
Calculation factor - k _r	0.02
Calculation factor - f ₀	14.7
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.017



NTN Bearing de Mexico, S.A.

EAN	7316577094995
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	17MM Bore; 30MM Outside Diameter; 7MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	61903
Weight / LBS	0.04
Outer Race Width	0.276 Inch 7 Millimeter
Outside Diameter	1.181 Inch 30 Millimeter
Bore	0.669 Inch 17 Millimeter
bore diameter:	17 mm
static load capacity:	2.55 kN
outside diameter:	30 mm
precision rating:	Not Rated



NTN Bearing de Mexico, S.A.

overall width:	7 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	7 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.3 mm
snap ring included:	Without Snap Ring
maximum rpm:	32000 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	4.62 kN
d_1	20.4 mm
D_2	27.7 mm
$r_{1,2}$ min.	0.3 mm
d_a min.	19 mm
D_a max.	28 mm
r_a max.	0.3 mm
Basic dynamic load rating C	4.62 kN
Basic static load rating C_0	2.55 kN
Fatigue load limit P_u	0.108 kN
Calculation factor k_r	0.02
Calculation factor f_0	14.7
Mass bearing	0.016 kg